E2 Fat Tire Bike Assembly Instructions

Description

How to install :	Picture	Size & Type of Tool Needed
• Fork		4mm allen wrench 5mm allen wrench 8mm wrench
• Handlebar		4 mm allen wrench
• Front wheel		19 mm wrench
• Front rack		3mm allen wrench 4mm allen wrench 8mm wrench

Instructions

Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Comments / Special Instructions
The fork hardware must be installed in the following order!	Place the handlebar neck over the fork tube stem	Secure cap then goto "Handlebar" step				
						
Align the handlebar to the fork and tighten the 2 screws on the neck						
						
	Left side of wheel always has the brake rotor					
						

E2 Fat Tire Bike Assembly Instructions

Description

How to install :	Picture	Size & Type of Tool Needed
• Rear rack		4mm allen wrench 5mm allen wrench
• Pedals		15 mm wrench
• Seat onto seat post		6mm allen wrench
• Seat onto bike		Quick Release seat post clamp

Instructions

Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Comments / Special Instructions
Rear rack frame 	Rear rack hardware 	Rear rack spacer position (2 sides) 		Attach rear rack to Seat post clamp 	Fully tighten rack screws 	
Pedals are marked with L & R 	Always turn **left pedal CCW** to tighten 	Always turn **right pedal CW** to tighten 				
Insert seat post clamp into seat 	Set to desired position and tighten clamp 					
Open quick release & adjust clamping force 	insert & set seat post to desired height 	Close quick release 				

E2 Fat Tire Bike Assembly Instructions

Description

Instructions

How to install :	Picture	Size & Type of Tool Needed	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Comments / Special Instructions

How adjust:	Picture	Size & Type of Tool Needed	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Picture/Instruction	Comments / Special Instructions
• Brake caliper		5mm allen							
									
• Handle bars		4mm allen							
									
• Shock Fork pressure adjustment		Air Chuck